

EDCON-COMPONENTS



T13G036


Technical Specifications:

Operating Temperature:
Rated Load:
Contact Resistance:
Insulation Resistance:
Withstanding Voltage:
Actuating Force:
Lifetime:

. -30°C ~ + 70°C
DC 30V / 0,5A
< 0,03 Ohm
> 100M Ohm
AC 500V (50Hz) 1min.
3 ~ 20N
5000 cycles

Technical Drawing:

CK-3.5-007	CK-3.5-007-1	CK-3.5-007-2	CK-3.5-007-3
CK-3.5-007G	CK-3.5-007G-1	CK-3.5-007G-2	CK-3.5-007G-3
CK-3.5-007H	CK-3.5-007H-1	CK-3.5-007H-2	CK-3.5-007H-3



3,5mm THT Audio jack	
Part No.:	T13G036
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	06.05.2007
APPD:	Schumi			FINISH	Jamy	Sheet	1 from 2


Copyright by EDCON-COMPONENTS H.Schmitt 11.6.2009

EDCON-COMPONENTS




Solder Profile

Lead Solder



Lead free Solder



Ordering Informations:

Item-No.	Circuit	ROHS	Packing			
T13G036	A	R	BU			

A	R= ROHS	BU= Bulk (Standard) TY= Tray Packing
B	N= Non	
C	ROHS	
D		

3,5mm THT Audio jack
Part No.: T13G036
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	06.05.2007
APPD:	Schumi			FINISH	Jamy	Sheet	2 from 2

Copyright by EDCON-COMPONENTS H.Schmitt 11.6.2009