



Technical Specification

| | |
|------------------------------|----------------------------------------------|
| Insulator: | Black glass filled polyester PPS-GF-30-FR |
| Flammability: | UL 94V-0 |
| Sleeve: | Brass CuZn 36Pb3 (36000) |
| Contact Clip (3finger): | Beryllium Copper (C17200) |
| Mating Pin: (Ø) | 0,38 to 0,50mm |
| Forces: | polished steel gauge(Ø)0,41mm |
| .-Insertion: | 0,5N typ. |
| .-Withdrawel: | 0,2N typ. |
| Mechanical Life: | min 500 cycles |
| Rated Current: | 1A |
| Contact Resistance: | max. 10m Ohm |
| Dielectric Strength: | min 500V rms |
| Minimal position of deliver: | 2 |
| Maximal position of deliver: | 50 |

Technical Drawing



Ordering Information

| Serie | No. of Pos. | Solder Pin Plating | Inner Clip Plating | ROHS | Packing |
|---------------|-------------|--------------------|--------------------|----------|-----------|
| T40006 | 50 | A | 3 | R | B1 |

| | | | | |
|----------------|-------------------------------------|--------------------------------------------|------------------------------------------------------|---------------------------------------------------|
| 02 ~ 50 | A= Tin 150µ" (Standard) | 1= Tin 150µ" 2= Tin 200µ" | R= ROHS conform N= NON ROHS conform | B1= Bulk 100PCS Ix = individuall |
| | B= Tin 200µ" C= GF | 3= GF (Standard) | | |
| | D= Gold 2µ" | 4= Gold 2µ" | | |
| | E= Gold 3µ" | 5= Gold 3µ" | | |
| | F= Gold 10µ" | 6= Gold 10µ" | | |
| | G= Gold 15µ" | 7= Gold 15µ" | | |
| | H=Special | 8=Special | | |

| | |
|------------------------------------------|---------------|
| Machined Contact Pitch 1,27mm | |
| Part No.: | T40006 |
| Customer: | |

| | | | | | | | |
|-------|-------|------|-------|--------|-------|-------|------------|
| DRW: | Jason | CHKD | Jules | MATL: | Wu | DATE | 06.06.2009 |
| APPD: | Join | | | FINISH | Shieh | Sheet | 1 from 1 |