



Name: Pushwire Cobnnector
 Packing: 100PCS in one Poly Bag
 Rated Voltage EN: 400V
 Rated Current: EN 24A
 Rated Voltage: CSA 600V
 Rated Current: CSA 20A
 Rated Voltage: UL 600V
 Rated Current: UL 20A
 Wire section area: Europe 1,0 ~ 2,5mm²
 Wire section area: AWG 14 ~ 12
 Color: Gray
 Wirng Direction: Frontage
 Type: nvenient wiring
 Dimension of Connector: (mm) 8,5 x 20,5 x 15,5
 Dimension of Connector: (") 0,335 x 0,807 x 0,61
 Pollution Rank: 2
 Withstanding the instanteneous peak V. 4KV
 Insulation Material: PA
 Anti burns rank UL V-0 / V-2
 Exhausted line length: 9-11mm
 Exhausted line length scope: 0,39in

Ordering Informations:

Item-No.	Circuit	Body Color	ROHS	Packing		
A17010	2	OR	R	BU		
only 2Pos.	OR= Orange	R= ROHS	BU= Bulk Ware			
		N= Non ROHS				

Cable Mount Pushwire Connector
Part No.: A17010
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	12.09.2009
APPD:	Jason			FINISH	Jamy	Sheet	1 from 1