



Technical Informations

Name:	Pushwire Cobnector
Packing:	100PCS in one Poly Bag
Rated Voltage EN:	400V
Rated Current: EN	24A
Rated Voltage: CSA	600V
Rated Current: CSA	20A
Rated Voltage: UL	600V
Rated Current: UL	20A
Wire section area: Europe	1,0 ~ 2,5mm ²
Wire section area: AWG	14 ~ 12
Color:	Blue
Wirng Direction:	Frontage
Type:	nvenient wiring
Dimension of Connector: (mm)	8,5 x 20,5 x 15,5
Dimension of Connector: (")	0,335 x 0,807 x 0,61
Pollution Rank:	2
Withstanding the instanteneous peak V.	4KV
Insulation Material:	PA
Anti burns rank UL	V-0 / V-2
Exhausted line length:	9-11mm
Exhausted line length scope:	0,39in

Ordering Informations:

Item-No.	Circuit	Body Color	ROHS	Packing		
A17011	4	BL	R	BU		
only 4Pos.	BL= Blue	R= ROHS	BU= Bulk Ware			
		N= Non ROHS				

Cable Mount Pushwire Connector	
Part No.:	A17011
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	12.09.2009
APPD:	Jason			FINISH	Jamy	Sheet	1 from 1