



Name: Pushwire Cobnector  
 Packing: 100PCS in one Poly Bag  
 Rated Voltage EN: 400V  
 Rated Current: EN 24A  
 Rated Voltage: CSA 600V  
 Rated Current: CSA 20A  
 Rated Voltage: UL 600V  
 Rated Current: UL 20A  
 Wire section area: Europe 1,0 ~ 2,5mm<sup>2</sup>  
 Wire section area: AWG 14 ~ 12  
 Color: Gray  
 Wirng Direction: Frontage  
 Type: nvenient wiring  
 Dimension of Connector: ( mm ) 8,5 x 20,5 x 15,5  
 Dimension of Connector: ( " ) 0,335 x 0,807 x 0,61  
 Pollution Rank: 2  
 Withstanding the instanteneous peak V. 4KV  
 Insulation Material: PA  
 Anti burns rank UL V-0 / V-2  
 Exhausted line length: 9-11mm  
 Exhausted line length scope: 0,39in

### Ordering Informations:

Item-No.	Circuit	Body Color	ROHS	Packing		
<b>A17013</b>	<b>8</b>	<b>GN</b>	<b>R</b>	<b>BU</b>		
<b>only 8Pos.</b>	<b>Green</b>	<b>R= ROHS</b>	<b>BU= Bulk Ware</b>			
		<b>N= Non ROHS</b>				

Cable Mount Pushwire Connector	
Part No.:	<b>A17013</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	12.09.2009
APPD:	Jason			FINISH	Jamy	Sheet	1 from 1