




**Technical Specification**

**Features**

- Wire Wound construction
- Polyolefin Shrink Tube
- Excellent Environmental Characteristics
- High reliability
- High Inductance and Lower RDC
- Tolerance 10% is standard tighter tolerance available

**Dimensions**



Part-No-	L	D	d
S10A09	22	11,0	0,8/+/-0,05

**Applications**

- Power Supplies
- SCR and Triac Controls
- RFI Suppression
- Filters
- Switching Regulators

**Electrical Characteristics**

**Technical Information**

Inductance Testing: LCR Bridge  
 measured @ 1KHz 0,1V HP4284A  
 RDC: Quad Tech 1880 Milliohmmeter  
 IDC Max. Lowewr inductance by 10%  
 Operating Temperature: -50°C ~ +125°C  
 Shrink Tube: Flame retardent UL type VW-1  
 Marking Inductance and tolerance  
 Note: All specifications subject to change without notice.

Inductance	Inductance Code	I Sat (max)	IDC (max)
680µH	681	1,050A	1,000A

DCR max.			
0,548Ω			

**THT AXIAL UL TUBE  
 POWER CHOKES**

Part No.: **S10A09**


Customer:

DRW:	James	CHKD	Jim	MATL:	Wim	DATE	06.08.2008
APPD:	Sarah			FINISH	Jeff	Sheet	1 from 2



**Soldering Profile**

**Classification Reflow Profile (JEDEC J-STD-020C)**



**Ordering Information**

Serie	Inductance	Tolerance	Function	ROHS	Packing
<b>S10A09</b>	<b>681</b>	<b>M</b>	<b>N</b>	<b>R</b>	<b>TB</b>

<b>681</b> = 680µH	<b>M</b> = Tol. 20%	<b>N</b> = No function	<b>R</b> = ROHS conform	<b>BU</b> = Bulk Ware
	<b>K</b> = Tol. 10%		<b>N</b> = NON ROHS conform	<b>TB</b> = Tape Box Package

**THT AXIAL UL TUBE  
POWER CHOKES**

Part No.: **S10A09**

Customer:

DRW:	James	CHKD	Jim	MATL:	Wim	DATE	06.08.2008
APPD:	Sarah			FINISH	Jeff	Sheet	2 from 2

