



Technical Specification


Features

- Wire Wound Construction
- Plastic Housing
- Excellent environmental characteristics
- Excellent Mechanical Strength
- Excelent Solderability
- High reliability

Applications

- VCR '2 PDP, LCD, TV set
- Automotive Systems
- Computer / Peripheral Equipment
- GPS, DC/Dc Converter, XDSL Modem
- Electronic Games
- Communications Equipment
- Genral Electronic Applications

Dimensions



Technical Dimensions

A (mm)	B (mm)	C (mm)	D (mm)
8,0	9,6	5,0 +/-0,3	0,6
E (mm)			
5,0			

Electrical Characteristics

Technical Information

Testing LCR Bridge, measured @ 1KHz 0,1V HP4284A
 Equivalent acceptacle
 RDC. QuadTech 1880 Milliohmmer
 IDC: Max. Lowers inductance by 10%
 Operating Temperature: -40°C ~ +105°C
 Storage Temperature: -40°C ~ +105°C
 Solder Methods: Vapor Phase, Infrared Reflow
 Marking: Inductance and tolerance
 Note: All specifications subject to change without notice.

Inductance	Inductance Code	IDC	DCR max.
100µH	101	0,670A	0,330Ω

THT Radial Encapsulated Power Choke

Part No.: **S10R25**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	02.05.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 2



Soldering Profile

Classification Reflow Profile (JEDEC J-STD-020C)



Ordering Information

Serie	Inductance	Tolerance	Lead Length	ROHS	Packing
S10R25	101	K	50	R	BU10

101 = 100µH	K = Tol. 10%	50 = 5mm	R = ROHS conform	BU = Bulk Ware
	J = Tol. 5%		N =NON ROHS conform	TY = Tray Package

THT Radial Encapsulated Power Choke	
Part No.:	S10R25
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	02.05.2009
APPD:	Join			FINISH	Shieh	Sheet	2 from 2

