



Technical Specification


Features

- Wire Wound Construction
- Plastic Housing
- Excellent environmental characteristics
- Excellent Mechanical Strength
- Excelent Solderability
- High reliability

Applications

- VCR '2 PDP, LCD, TV set
- Automotive Systems
- Computer / Peripheral Equipment
- GPS, DC/Dc Converter, XDSL Modem
- Electronic Games
- Communications Equipment
- Genral Electronic Applications

Dimensions



Technical Dimensions

A (mm)	B (mm)	C (mm)	D (mm)
14,0	17,0	5,0 +/-0,3	0,6
E (mm)			
5,0			

Electrical Characteristics

Technical Information

Testing LCR Bridge, measured @ 1KHz 0,1V HP4284A
 Equivalent acceptacle
 RDC. QuadTech 1880 Milliohmmeter
 IDC: Max. Lowers inductance by 10%
 Operating Temperature: -40°C ~ +105°C
 Storage Temperature: -40°C ~ +105°C
 Solder Methods: Vapor Phase, Infrared Reflow
 Marking: Inductance and tolerance
 Note: All specifications subject to change without notice.

Inductance	Inductance Code	IDC	DCR max.
1500µH	152	0,680A	1,300Ω

THT Radial Encapsulated Power Choke

Part No.: **S10R28**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	02.05.2009
APPD:	Join			FINISH	Shieh	Sheet	1 from 2



Soldering Profile

Classification Reflow Profile (JEDEC J-STD-020C)



Ordering Information

Serie	Inductance	Tolerance	Lead Length	ROHS	Packing
S10R28	152	K	50	R	BU10

152= 1500µH	K= Tol. 10%	50= 5mm	R= ROHS conform	BU= Bulk Ware
	J= Tol. 5%		N= NON ROHS conform	TY= Tray Package

THT Radial Encapsulated Power Choke	
Part No.:	S10R28
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	02.05.2009
APPD:	Join			FINISH	Shieh	Sheet	2 from 2

