

# EDCON-COMPONENTS



**Material:** Aluminium  
**Input Voltage:** 12VDC/AC / 100-240VAC  
**Power:** 3x1W  
**Luminous Flux:** 90-100Lm/W  
**Beam Angle:** 15° / 30° / 45° / 50°  
**Color Temperature:** Cool White / Warm White / Y / R / B / G  
**Lifetime:** 50000Hours  
**Lamp Head can be adjusted:** +/- 60°



## Ordering Information

Serie	Beam Angle	Color	Power	Voltage	Front Surface	ROHS	Packing
-------	------------	-------	-------	---------	---------------	------	---------

<b>M27033</b>	<b>15</b>	<b>CW</b>	<b>A</b>	<b>1</b>	<b>E</b>	<b>R</b>	<b>CA</b>
---------------	-----------	-----------	----------	----------	----------	----------	-----------

<b>15=</b> Beam Angle 15°	<b>CW=</b> Cool White	<b>A=</b> 3x1Watt	<b>1=</b> 12VAC/DC	<b>E=</b> Aluminium	<b>R=</b> Rohs Conform	<b>CA=</b> Carton
<b>30=</b> Beam Angle 30°	<b>WW=</b> Warm White		<b>2=</b> 100-240VAC		<b>N=</b> NON RohsConfor	
<b>45=</b> Beam Angle 45°	<b>YE=</b> Yellow					
<b>50=</b> Beam Angle 50°	<b>RD=</b> Red					
	<b>BL=</b> Blue	<b>GN=</b> Green				

<b>Ceiling Light for Indoor use</b>	
Part No.:	<b>M27033</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	20.09.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 1

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)