

# EDCON-COMPONENTS



## Technical Informations

### Physical

Dimension £-86x54x0.8 (+/- 0.04 )mm

Weight £-5.8g +/-0.5

### Materials

PVC or PET

### Packaging

200pcs per box, 2000pcs per carton, 14kgs/carton

### Specials options

Offset printing, screen printing, Personalization printing

Signature stripe

Magnetic stripe --350Oe, 650Oe, 2750Oe, 4000Oe

Serial Number--ink jet, thermo printing, laser engraving

### IC available at 125KHz nominal

TK4100, EM4100, EM4102, EM4450,

NXP Hiatg1, Hitag2, HitagS256, HitagS2048,

Atmel temic 5567

### IC available at 13.56MHz nominal

NXP Mifare1 S50, Mifare1 S70, Desfire MF3ICD40,

Mifare Ultralight, Icode1, Icode Sli , Legic mim256, JWL872,

TI256, TI2048INSIDE picopass 2KS

**R7 versions is for dual interface card, to add another contact chip,**

**available to punch a slot**

**RFID ISO Card**

Part No.: **T97005**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	22.02.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 1

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)