

EDCON-COMPONENTS



SPECIFICATION:


Contact Rating:	15VA
Pull In Value (PI):	110~300AT
Drop Out Value (DO):	≥ 25AT
Contact Resistance:	≤ 200mΩ
Breakover Voltage:	≥ 500VDC
Insulation Resistance:	≥ 100MΩ
Electrostatic Capacitance:	2,0pf
Max. Switching Voltage:	220VAC
Max. Switching Current:	1A
Max. Carry Current:	2A
Operaing time:	≤ 1,2ms
Bounce Time:	≤ 1ms
Release Time:	≤ 0,4ms
Maximum Operating Freq.:	200Hz
Operating Temperature:	. -10°C ~ +70°C

Description



Reed contacts are hermetically sealed within a glass tube and do not receive the external atmospheric environment;
 Quick response, and light weight;
 Superior corrosion resistance and wear resistance of the contacts assures stable switching operation and long life;
 Composed fast with the coil and magnet, reed switch can be used for reed relay or sensor;
 Widely used in household appliances, control equipment, communication equipment, communication, automotive electronic

Drawing

常开型NO type



转换型Changeover type



Reed Switch 8x50mm

Part No.: **Q39102**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	25.02.2014	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No. XGH-8Z		1 from 2	

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	Contact form	Pull In Value	Special function	Special function	ROHS	Packing				
Q39102	2	A	1	X	R	BU				

	A= Pull in Value 110-180	1= No special function	X= No special function	N= Non ROHS	BU= Bulk Ware	
2= contact form 1C	B= Pull in Value 180-240			R= ROHS conform		
	C= Pull in Value 240-300					

Reed Switch 8x50mm	
Part No.:	Q39102
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	25.02.2014
APPD:	Schumi			FINISH	Jamy		Sheet No. XGH-8Z		2 from 2