



**Technical Spezification**

spring din rail terminal block, 4-conductor through, front-entry terminal blocks, spring cage clamp wire connection of wago 279 series style terminals.

Conductors	4
Wire Range:	0,2~1,5mm"
Wire Range	24~16 AWG
Rated Voltage:	800V /IEC) 600V(UL)
Rate Current:	18A (IE) , 10A(UL)
Insulating Material:	Nylon PA66 (UL94,V-0 or V-2)
Spring Cage Materials:	Spring Steel
Stripping Length:	8~9mm / 0,33

**Dimension**

Thickness:	4mm
Width:	73mm
Height:	27mm (din Rail Type 35x7,5)
Color of Body:	Gray, Orange, Red, Blue, Yellow

**Ordering Information**

Serie	Color of Body	ROHS	Packing			
<b>A29003</b>	<b>GY</b>	<b>R</b>	<b>BX</b>			

<b>GY=</b> Gray	<b>R=</b> ROHS Conform	<b>BU=</b> Bulk-Ware
<b>OR=</b> Orange		
<b>RD=</b> Red	<b>N=</b> NON ROHS Conform	<b>BX=</b> Box Packing
<b>BL=</b> Blue		
<b>YE=</b> Yellow		<b>IV=</b> Individuel Packing

<b>DIN-Rail Terminal Block</b>	
Part No.:	<b>A29003</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	18.08.2011
APPD:	Schumi			FINISH	Jamy	Sheet	1 from 1

