



### Technical Spezification

din rail mounted terminals, spring cage clamp terminals offer a more time saving than the screw clamp connection, the 206A is equivalent wago connector 282-901

Conductors	2
Wire Range:	0,2~6,0mm"
Wire Range	24~10 AWG
Rated Voltage:	800V /IEC) 600V(UL)
Rate Current:	41A (IE) , 30A(UL)
Insulating Material:	Nylon PA66 (UL94,V-0 or V-2)
Spring Cage Materials:	Spring Steel
Stripping Length:	12~13mm / 0,49

### Dimension

Thickness:	8mm
Width:	74,5mm
Height:	32,5mm (din Rail Type 35x7,5)
Color of Body:	Gray, Blue, Orange,

### Ordering Information

Serie	Color of Body	ROHS	Packing			
<b>A29017</b>	<b>GY</b>	<b>R</b>	<b>BX</b>			

<b>GY=</b> Gray	<b>R=</b> ROHS Conform	<b>BU=</b> Bulk-Ware
<b>BL=</b> Blue	<b>N=</b> NON ROHS Conform	<b>BX=</b> Box Packing
<b>OR=</b> Orange		
		<b>IV=</b> Individuel Packing

<b>DIN-Rail Terminal Block</b>	
Part No.:	<b>A29017</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	DATE	18.08.2011
APPD:	Schumi			FINISH	Jamy	Sheet	1 from 1

