

EDCON-COMPONENTS



This picture are only a example from the product specification. Every further development changing the construction of the case



Features

Designed for Outdoor signage, decorating or lighting applications
Constant Voltage Output
Resin potted and Waterproof
Aluminium housing
Complies with CE Standard

Technical Specifications

Input Voltage: 170~250VAC / 50/60Hz
Max. Power: 40 Watt
Output Type: Constant Voltage
Dimming: No
Built in active PFC: No
Power Factor: Low
Efficiency: 86%
AC inrush current (max.): Cold start, 40A@230VAC
Output Voltage: 12VDC $\pm 5\%$
Output Current: 3,4A max.
Overload protection: 105% hiccup mode, auto-recovery
Overvoltage Protection: 120% rated output voltage
Withstand voltage: I/P~O/P; 1,5KVAC, 1 minute
Operating Temperature: -25°C ~ +40°C
Installation: Outdoor waterproof
IP rating: IP 66
Cooling: Free air convection
Certifications (standard): CE
Connection input/output: Input:0,75mm²x3 (length 180mm) Output 0,75mm²x2 180mm
Dimensions (LxWxH): ca. 230x38x26mm
Weight:(kg) ca. 0,41

**Waterproof Constant
Voltage Power Supply**

Part No.: **L40004**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2	

Customer:
email: info@edcon-components.com

www.edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	Special function	ROHS	Packing							
-------	------------------	------	---------	--	--	--	--	--	--	--

L40004	-	X	R	S						
---------------	---	----------	----------	----------	--	--	--	--	--	--

X= No function	R= ROHS Conform	S= Standard Packing
----------------	-----------------	---------------------

Waterproof Constant Voltage Power Supply

Part No.: **L40004**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2	

Customer: