

# EDCON-COMPONENTS



This picture are only a example from the product specification. Every further development changing the construction of the case



## Features

Designed for Outdoor signage, decorating or lighting applications  
Constant Voltage Output  
Resin potted and Waterproof  
Aluminium housing  
Complies with CE Standard

## Technical Specifications

Input Voltage:	180~260VAC / 50/60Hz
Max. Power:	30 Watt
Output Type:	Constant Current
Dimming	No
Built in active PFC:	No
Power Factor:	Low
Efficiency:	86%
Output Voltage:	14~28 VDC
Output Current:	1050mA
Overload protection:	107% rated output voltage
Withstand voltage:	I/P~O/P; 1,5KVAC, 1 minute
Operating Temperature:	. -25°C ~ +40°C
Installation:	Outdoor waterproof
IP rating:	IP 66
Cooling:	Free air convection
Certifications ( standard):	CE
Connection input/output:	Input:0,75mm²x3 (length 180mm) Output 0,75mm²x2 180mm
Dimensions (LxWxH):	ca. 200x35x25mm
Weight:(kg)	ca. 0,25

**Waterproof Constant  
Current Power Supply**

Part No.: **L40023**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2	

Customer:

# EDCON-COMPONENTS



## Ordering Informations

Serie	Special function	ROHS	Packing							
-------	------------------	------	---------	--	--	--	--	--	--	--

<b>L40023</b>	-	<b>X</b>	<b>R</b>	<b>S</b>						
---------------	---	----------	----------	----------	--	--	--	--	--	--

<b>X</b> = No function	<b>R</b> = ROHS Conform	<b>S</b> = Standard Packing
------------------------	-------------------------	-----------------------------

**Waterproof Constant  
Current Power Supply**

Part No.: **L40023**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	04.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2	

Customer: