EDCON-COMPONENTS







Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Technical Informations

| Size of LED | 3528 |
|--------------------------------|------------------|
| LED per Meter | 36PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 2,88Watt |
| Emitting Color of LED Strip | Warm White 3000K |
| Lumen per Meter | 216lm |
| Protection Degree | IP67 |

| | | | | | | | | LED RIGID BAR Strip LED Type 3528 | | | |
|---|--------|------|--------|--------|--------|-----------|-------|--------------------------------------|------------|-----------|----------|
| | | | | | | | | | | Part No.: | M26A1026 |
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 08.02.2012 | Customer: | |
| APPD: | Schumi | | | FINISH | Jamy | | Shee | t No. | 1 from 3 | Customer. | |
| www.edcon-components.com email: info@edcon-components.com | | | | | | | | | | | |

Copyright by EDCON-COMPONENTS

EDCON-COMPONENTS









Connector Configurator



Protection Degree IP68 Type A2 Male and Female for two Wires Type A4 Male and Female for four Wires



Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires



Protection Degree IP50 Type E4 Male and Female for four Wires




Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires





| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 08.02.2012 | Customor |
|---|--------|------|--------|--------|--------|-----------|-----------|------|------------|-----------|
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 2 from 3 | Customer: |
| www.edcon-components.com email: info@edcon-components.com | | | | | | | | | | |

Copyright by EDCON-COMPONENTS

om

EDCON-COMPONENTS



The Power of LED Light

Ê,

RoHS Lead Free

Ordering Informations

| M26A1026 - OO X X R TR 00= without any connector on both side (Standard w/o Connector) X= No special function X= No special function R= ROHS Conform TR= Tape / Reel N= NON ROHS Connector) N= NON ROHS Conform N= NON ROHS Conform A2= Type A2 Male + Female type for 2 Wires (look connector configurator) Vires (look connector | Part-No. | Connector | Special function | Special function | ROHS | Packing | |
|---|------------|--|------------------|------------------|---------------------------|---------|--|
| Any connector on both side (Standard w/o Connector) X= No special function X= No special function Conform Reel N= NON ROHS Conform N= NON ROHS Conform A2= Type A2 Male + Female type for 2 Wires (look connector Vertical Ve | M26A1026 - | 00 | Х | Х | R | TR | |
| Connector) Conform A2= Type A2 Male + Female type for 2 Wires (look connector Conform | | any connector on both side | • | | Conform N = NON | | |
| Male + Female type for 2 Wires (look connector | | Connector) | | | | | |
| | | Male + Female type for 2 Wires (look | | | | | |

LED RIGID BAR Strip LED Type 3528 Part No.: M26A1026 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP