EDCON-COMPONENTS







The Power of LED Light

Technical Informations

Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	3528
LED per Meter	96PCS
Voltage of LED Strip	12Volt
Power of LED Strip	7,68Watt
Emitting Color of LED Strip	Cool White 6000K
Lumen per Meter	624lm
Protection Degree	IP67

							LED RIGID BAR Strip LED Type 3528				
										Part No.:	M26A1034
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	
amail: infa@adaan companyate com											

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

A MEMBER OF EDCON-GROUP

EDCON-COMPONENTS









Connector Configurator



1111

Protection Degree IP68 Type A2 Male and Female for two Wires Type A4 Male and Female for four Wires

Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires



Protection Degree IP50 Type E4 Male and Female for four Wires

Jason

Schumi

CHKD



Protection Degree IP50 Type F2 Male and Female for two Wires

MATL:

FINISH

Wilson



Mason

Sheet No.

DATE

Protection Degree IP20 Type G2 Male and Female for two Wires



	Type 3528				
	Part No.:	M26A1034			
08.02.2012	Customer:				
2 from 3	Customer.				

www.edcon-components.com

DRW:

APPD:

Copyright by EDCON-COMPONENTS

TOLERANCE

Wilson

Jamy

email: info@edcon-components.com

EDCON-COMPONENTS



The Power of LED Light

Ê,

RoHS Lead Free

Ordering Informations

M26A1034 - OO X X R TR 00= without any connector on both side (Standard w/o Connector) X= No special function X= ROHS Conform TR= Tape / Reel N= NON ROHS Conform N= NON ROHS Conform N= NON ROHS Conform A2= Type A2 Male + Female type for 2 Wires (look connector Wires (look connector Vires (look connector	Part-No.	Connector	Special function	Special function	ROHS	Packing	
Any connector on both side (Standard w/o Connector) X= No special function X= No special function Conform Reel N= NON ROHS Conform A2= Type A2 Male + Female type for 2 Wires (look A= No special function N= NON ROHS Conform	M26A1034 -	00	Х	Х	R	TR	
(Standard w/o ROHS Connector) Conform A2= Type A2 Male + Female type for 2 Wires (look		any connector	-		Conform	-	I
Male + Female type for 2 Wires (look		(Standard w/o			ROHS		
configurator)		Male + Female type for 2 Wires (look connector					

Type 3528 Part No.: M26A1034 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

LED RIGID BAR Strip LED

COMPONENTS A MEMBER OF EDCON-GROUP