### **EDCON-COMPONENTS**

REACH







Applications

**Technical Informations** 

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

#### **Features**

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	3528		
LED per Meter	180PCS		
Voltage of LED Strip	12Volt		
Power of LED Strip	14,4Watt		
Emitting Color of LED Strip	Red		
Lumen per Meter	360lm		
Protection Degree	IP67		

											BAR Strip LED be 3528
										Part No.:	M26A1040
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Cusionier.	
www.edcon-components.com email: info@edcon-components.com											

### Copyright by EDCON-COMPONENTS

# **EDCON-COMPONENTS**



Protection Degree IP68

Male and Female for two Wires

Male and Female for four Wires

Type A2

Type A4







**Connector Configurator** 



1111

Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires




Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



_										Tart No	
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	2 from 3	Customer.	
www.edcon-components.com email: info@edcon-components.com											

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

# **EDCON-COMPONENTS**



The Power of LED Light

Ê,

RoHS Lead Free

**Ordering Informations** 

Part-No.	Connector	Special function	Special function	ROHS	Packing	
M26A1040 -	00	Х	Х	R	TR	
	<b>00</b> = without any connector on both side (Standard w/o Connector)	X= No special function	<b>X</b> = No special function	R= ROHS Conform N= NON ROHS Conform	<b>TR</b> = Tape / Reel	
	A2= Type A2 Male + Female type for 2 Wires (look connector configurator)					

Type 3528 Part No.: M26A1040 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

LED RIGID BAR Strip LED

COMPONENTS A MEMBER OF EDCON-GROUP