EDCON-COMPONENTS







Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of,

to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

recnnical	Informations

Size of LED	5050
LED per Meter	30PCS
Voltage of LED Strip	12Volt
Power of LED Strip	7,2Watt
Emitting Color of LED Strip	Yellow
Lumen per Meter	180lm
Protection Degree	IP67

											BAR Strip LED be 5050
										Part No.:	M26A2004
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	
www.edcon-components.com email: info@edcon-components.com											

Copyright by EDCON-COMPONENTS

EDCON-COMPONENTS









Connector Configurator



1111

Protection Degree IP68 Type A2 Male and Female for two Wires Type A4 Male and Female for four Wires

Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires




Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customor	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	2 from 3	Customer:	
www.edcon-components.com email: info@edcon-components.cor									omponents.com		

Copyright by EDCON-COMPONENTS

M26A2004

EDCON-COMPONENTS



The Power of LED Light

Ê,

RoHS Lead Free

Ordering Informations

M26A2004 - OO X X R TR 00= without any connector on both side (Standard w/o Connector) X= No special function X= ROHS Conform TR= Tape / Reel N= NON ROHS Conform N= NON ROHS Conform N= NON ROHS Conform A2= Type A2 Male + Female type for 2 Wires (look connector Wires (look connector	Part-No.	Connector	Special function	Special function	ROHS	Packing	
any connector on both side (Standard w/o Connector) X= No special function Conform Reel A2= Type A2 Male + Female type for 2 Wires (look A2= No special function N= NON ROHS Conform	M26A2004 -	00	Х	Х	R	TR	
(Standard w/o Connector) A2= Type A2 Male + Female type for 2 Wires (look		any connector	-	-	Conform	-	
Male + Female type for 2 Wires (look		(Standard w/o			ROHS		
configurator)		Male + Female type for 2 Wires (look connector				•	

LED RIGID BAR Strip LED Type 5050 Part No.: M26A2004 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP