EDCON-COMPONENTS







The Power of LED Light

Technical Informations

Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	5050
LED per Meter	48PCS
Voltage of LED Strip	12Volt
Power of LED Strip	11,4Watt
Emitting Color of LED Strip	Cool White 5500K
Lumen per Meter	936lm
Protection Degree	IP67

											BAR Strip LED pe 5050
										Part No.:	M26A2021
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

EDCON-COMPONENTS



Type A2

Type A4







Connector Configurator



Protection Degree IP68 Male and Female for two Wires



Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires



Male and Female for four Wires


Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



LED RIGID BAR Strip LED Type 5050							
Part No.:	M26A2021						
Customer:							

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customor	
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3	- Customer:	
www.edcon-components.com email: info@edcon-components.com											

Copyright by EDCON-COMPONENTS

EDCON-COMPONENTS



The Power of LED Light

E

RoHS Lead Free

Ordering Informations

M26A2021 - OO X X R TR 00= without any connector on both side (Standard w/o Connector) X= No special function X= No special function R= ROHS Conform TR= Tape / Reel N= NON ROHS Conform X= No special function N= NON ROHS Conform	Part-No.	Connector	Special function	Special function	ROHS	Packing	
00= without any connector on both side (Standard w/o Connector) X= No special function X= No special function R= ROHS Conform TR= Tape / Reel N= NON ROHS Conform N= NON ROHS	M26A2021 -	00	Х	Х	R	TR	
any connector on both side (Standard w/o Connector) X= No Special function X= No Special function Conform Reel M= NON ROHS Conform N= NON ROHS							
on both side N= NON (Standard w/o ROHS Connector) Conform			-				
A2 = Type A2		(Standard w/o	Tunction	Tunction	ROHS		
Male + Female type for 2 Wires (look connector configurator)		Male + Female type for 2 Wires (look connector					

LED RIGID BAR Strip LED Type 5050 Part No.: M26A2021 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP