

# EDCON-COMPONENTS



The Power of LED Light



## Applications

It used perfectly in order to illuminate common objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

## Features

Available in DC 12Volt or DC 24Volt maximum  
 Operating Temperature: -20°C ~ +50°C  
 Long Life span LED light, more than 50000hours  
 Viewing Angle of LED 120°  
 Available in Different White areas  
 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip  
 Length: 1000mm  
 Width: 15mm  
 Thickness: 7mm

## Technical Informations

Size of LED	5050
LED per Meter	48PCS
Voltage of LED Strip	12Volt
Power of LED Strip	11,4Watt
Emitting Color of LED Strip	Warm White 2700K
Lumen per Meter	864lm
Protection Degree	IP67

**LED RIGID BAR Strip LED  
Type 5050**

Part No.: **M26A2026**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 3

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



The Power of LED Light



## Connector Configurator



Protection Degree IP68  
**Type A2**  
 Male and Female for two Wires  
**Type A4**  
 Male and Female for four Wires



Protection Degree IP68  
**Type B2**  
 Male and Female for two Wires  
**Type B4**  
 Male and Female for four Wires



Protection Degree IP68  
**Type C2**  
 Male and Female for two Wires  
**Type C4**  
 Male and Female for four Wires



Protection Degree IP50  
**Type D2**  
 Male and Female for two Wires



Protection Degree IP50  
**Type E4**  
 Male and Female for four Wires



Protection Degree IP50  
**Type F2**  
 Male and Female for two Wires



Protection Degree IP20  
**Type G2**  
 Male and Female for two Wires

**LED RIGID BAR Strip LED  
 Type 5050**

Part No.: **M26A2026**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



The Power of LED Light



## Ordering Informations

Part-No.	Connector	Special function	Special function	ROHS	Packing	
M26A2026	OO	X	X	R	TR	

<b>00</b> = without any connector on both side (Standard w/o Connector)	<b>X</b> = No special function	<b>X</b> = No special function	<b>R</b> = ROHS Conform <b>N</b> = NON ROHS Conform	<b>TR</b> = Tape / Reel
<b>A2</b> = Type A2 Male + Female type for 2 Wires (look connector configurator)				

<b>LED RIGID BAR Strip LED Type 5050</b>	
Part No.:	<b>M26A2026</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3