EDCON-COMPONENTS







The Power of LED Light

Technical Informations

Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	5050
LED per Meter	60PCS
Voltage of LED Strip	12Volt
Power of LED Strip	14,4Watt
Emitting Color of LED Strip	Cool White 4200K
Lumen per Meter	1170lm
Protection Degree	IP67

											BAR Strip LED pe 5050
										Part No.:	M26A2034
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	
										mail into @ada	

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

EDCON-COMPONENTS









Connector Configurator



Protection Degree IP68

Male and Female for two Wires

Male and Female for four Wires

Type A2

Type A4

1111

Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires




Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



										Fait NO	IVIZOAZU34
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customor:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	2 from 3	2 from 3	
www.edcon-components.com email: info@edcon-components.com											

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

M26A2024

EDCON-COMPONENTS



The Power of LED Light

E,

RoHS Lead Free

Ordering Informations

Part-No.	Connector	Special function	Special function	ROHS	Packing	
M26A2034 -	00	Х	Х	R	TR	
	00 = without any connector on both side	X = No special function	X = No special function	R= ROHS Conform N= NON	TR = Tape / Reel	
	(Standard w/o Connector)			ROHS Conform		
	A2= Type A2 Male + Female type for 2 Wires (look connector configurator)					
	,					

LED RIGID BAR Strip LED Type 5050 Part No.: M26A2034 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP