EDCON-COMPONENTS







Applications

Technical Informations

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	5050
LED per Meter	48PCS
Voltage of LED Strip	24Volt
Power of LED Strip	11,4Watt
Emitting Color of LED Strip	Red
Lumen per Meter	288lm
Protection Degree	IP67

DRW: Jason CHKD Wilson MATL: Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Jamy Sheet No. 1 from 3	LED RIGID BAR Strip LE Type 5050											
											Part No.:	M26A2071
APPD: Schumi FINISH Jamy Sheet No. 1 from 3	DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customor	
	APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

EDCON-COMPONENTS



Protection Degree IP68

Male and Female for two Wires

Male and Female for four Wires

Type A2

Type A4



The Power of LED Light





Connector Configurator





Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires



Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



LED RIGID BAR Strip LED Type 5050 Part No.: M26A2071

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3	Customer.
www.edcon-components.com email: info@edcon-components.com										

Copyright by EDCON-COMPONENTS

EDCON-COMPONENTS



The Power of LED Light

Ø

RoHS Lead Free

Ordering Informations

Part-No.	Connector	Special function	Special function	ROHS	Packing	
M26A2071 -	00	Х	Х	R	TR	
					-	
	00 = without any connector	X = No special function	X = No special function	R = ROHS Conform	TR = Tape / Reel	
	on both side (Standard w/o Connector)	Tunction	Tunction	N = NON ROHS Conform		
	A2= Type A2 Male + Female type for 2 Wires (look connector configurator)					
-						

LED RIGID BAR Strip LED Type 5050 Part No.: M26A2071 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP