EDCON-COMPONENTS











Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip

Length: 1000mm Width: 15mm Thickness: 7mm

Technical Informations

Size of LED	5050	
LED per Meter	48PCS	
Voltage of LED Strip	24Volt	
Power of LED Strip	11,4Watt	
Emitting Color of LED Strip	Green	
Lumen per Meter	576lm	
Protection Degree	IP67	

LED RIGID BAR Strip LED Type 5050

Part No.: **M26A2072**

Customer:

DRW: CHKD Wilson MATL: Wilson 08.02.2012 **TOLERANCE** Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 3

email: info@edcon-components.com

www.edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Connector Configurator



Protection Degree IP68

Type A2

Male and Female for two Wires

Type A4

Male and Female for four Wires



Protection Degree IP68

Type B2

Male and Female for two Wires

Type B4

Male and Female for four Wires



Protection Degree IP68

Type C2

Male and Female for two Wires

Type C4

Male and Female for four Wires



Protection Degree IP50 **Type D2**Male and Female for two Wires



Protection Degree IP50 **Type E4**Male and Female for four Wires



Protection Degree IP50 **Type F2**Male and Female for two Wires



Protection Degree IP20 **Type G2**Male and Female for two Wires

LED RIGID BAR Strip LED Type 5050

Part No.: **M26A2072**

Customer:

DRW: CHKD Wilson MATL: 08.02.2012 Jason Wilson **TOLERANCE** Mason DATE APPD: Schumi FINISH Sheet No. Jamy 2 from 3

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

|--|

M26A2072

Connector	Special function	Special function	ROHS	Packing	
00	Χ	Х	R	TR	

00 = without any connector	X= No special function	X= No special function	R= ROHS Conform	TR= Tape / Reel
on both side		Tariotion	N= NON	
(Standard w/o			ROHS	
Connector)			Conform	
A2 = Type A2				
Male + Female				
type for 2				
Wires (look				
connector				
configurator)				

LED RIGID BAR Strip LED Type 5050

Part No.: **M26A2072**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 APPD: Schumi FINISH Sheet No. 3 from 3 Jamy

Customer: