## **EDCON-COMPONENTS**







The Power of LED Light

**Technical Informations** 

Applications

It used perfectly in order to illuminate commun objects, like displays, boards, refrigerator, and racks, Besides that, they can be used in any way you can think of, to add something exceptional to the atmosphere. Waterproof serie

#### Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of RIGID-BAR LED-Strip Length: 1000mm Width: 15mm Thickness: 7mm

Size of LED	5050
LED per Meter	72PCS
Voltage of LED Strip	24Volt
Power of LED Strip	17,4Watt
Protection Degree	IP67

Emitting Color of LED Strip	Lumen per Meter
Red	144lm
Green	288lm
Blue	180lm

											BAR Strip LED be 5050
										Part No.:	M26A2112
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 3	Customer.	

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

A MEMBER OF EDCON-GROUP

# **EDCON-COMPONENTS**



Type A2

Type A4



The Power of LED Light





## **Connector Configurator**



Protection Degree IP68 Male and Female for two Wires



Protection Degree IP68 Type B2 Male and Female for two Wires Type B4 Male and Female for four Wires



Protection Degree IP68 Type C2 Male and Female for two Wires Type C4 Male and Female for four Wires



Protection Degree IP50 Type D2 Male and Female for two Wires



Male and Female for four Wires


Protection Degree IP50 Type E4 Male and Female for four Wires



Protection Degree IP50 Type F2 Male and Female for two Wires



Protection Degree IP20 Type G2 Male and Female for two Wires



LED RIGID BAR Strip LED Type 5050					
Part No.:	M26A2112				
Customer:					

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2012	Customor
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3	Customer:
www.edcon-components.com email: info@edcon-components.com										

Copyright by EDCON-COMPONENTS

email. mo@eucon-components.com

# **EDCON-COMPONENTS**



REACH The Power of LED Light

Ê,

RoHS Lead Free

**Ordering Informations** 

Part-No.		Connector	Special function	Special function	ROHS	Packing	
M26A2112	-	00	Х	Х	R	TR	
		<b>00</b> = without any connector	X= No special function	<b>X</b> = No special function	<b>R</b> = ROHS Conform	<b>TR</b> = Tape / Reel	
		on both side	Turretion	Turretion	N= NON		
		(Standard w/o			ROHS		
		Connector)		l	Conform		
		A2= Type A2 Male + Female type for 2 Wires (look connector configurator)					

LED RIGID BAR Strip LED Type 5050 Part No.: M26A2112 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 08.02.2012 Customer: APPD: Schumi FINISH Sheet No. 3 from 3 Jamy www.edcon-components.com

### Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

COMPONENTS A MEMBER OF EDCON-GROUP