

# EDCON-COMPONENTS



The Power of LED Light



## Applications

Ideal for Indoor applications e.g. under cupboard, stairs, indirect lighting applications, a.s.o.

## Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED lights, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length= 5000mm

Width= Small=6 or Medium=8mm

Thickness: 2,2mm

## Technical Informations

|                             |                  |
|-----------------------------|------------------|
| Size of LED                 | 3528             |
| LED per Meter               | 120PCS           |
| Voltage of LED Strip        | 24Volt           |
| Power of LED Strip          | 9,6Watt          |
| Emitting Color of LED Strip | Warm White 3000K |
| Lumen per Meter             | 720lm            |
| Protection Degree           | IP20             |

**LED Flex-Strip LED-Size  
3528**

Part No.: **M33A1117**

|       |        |      |        |        |        |           |           |      |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE | 06.02.2012 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. |      | 1 from 2   |

Customer:

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



The Power of LED Light



## Ordering Informations

| Part-No. | Special function | ROHS | Packing |  |  |  |
|----------|------------------|------|---------|--|--|--|
| M33A1117 | X                | R    | TR      |  |  |  |

|                        |                     |                 |
|------------------------|---------------------|-----------------|
| X= No special function | R= ROHS Conform     | TR= Tape / Reel |
|                        | N= NON ROHS Conform |                 |

|   |                 |
|---|-----------------|
| <b>LED Flex-Strip LED-Size<br/>3528</b> |                 |
| Part No.:                               | <b>M33A1117</b> |
| Customer:                               |                 |

|       |        |      |        |        |        |           |           |      |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE | 06.02.2012 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. |      | 2 from 2   |

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)