

EDCON-COMPONENTS



The Power of LED Light



Applications

It is made with Epoxy Cove, Suitable for use in humid locations such as bathrooms and for use outdoors for example on garden furniture or accent lighting on house and buildings.

Features

Available in DC 12Volt or DC 24Volt maximum
 Operating Temperature: -20°C ~ +50°C
 Long Life span LED light, more than 50000hours
 Viewing Angle of LED 120°
 Available in Different White areas
 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip
 Length= 5000mm
 Width= 10mm
 Thickness: 2,5mm

Technical Informations

| | |
|-----------------------------|---------|
| Size of LED | 3528 |
| LED per Meter | 60PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 4,8Watt |
| Emitting Color of LED Strip | Red |
| Lumen per Meter | 120lm |
| Protection Degree | IP65 |

**LED Flex-Strip LED-Size
3528**

Part No.: **M33A2027**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 1 from 2 |

Customer:

EDCON-COMPONENTS



The Power of LED Light



Ordering Informations

| Part-No. | Special function | ROHS | Packing | | | |
|----------|------------------|------|---------|--|--|--|
| M33A2027 | X | R | TR | | | |

| | | |
|------------------------|---------------------|-----------------|
| X= No special function | R= ROHS Conform | TR= Tape / Reel |
| | N= NON ROHS Conform | |

LED Flex-Strip LED-Size 3528

Part No.: **M33A2027**

| | | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 | Customer: |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 2 from 2 | | |