EDCON-COMPONENTS











Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 4,0mm

Technical Informations

Size of LED	3528
LED per Meter	30PCS
Voltage of LED Strip	12Volt
Power of LED Strip	2,4Watt
Emitting Color of LED Strip	Red
Lumen per Meter	60lm
Protection Degree	IP67

LED Flex-Strip LED-Size 3528


Part No.: **M33A3001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2

email: info@edcon-components.com

Customer:

EDCON-COMPONENTS











Ordering Informations

Part-No.

M33A3001

Special function	ROHS	Packing		
Y	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel	
Turiction	N = NON		
	ROHS		
	Conform		
		=	

LED Flex-Strip LED-Size 3528

Part No.: M33A3001

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: