# **EDCON-COMPONENTS**











# Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 4,0mm

#### **Technical Informations**

Size of LED	3528
LED per Meter	30PCS
Voltage of LED Strip	12Volt
Power of LED Strip	2,4Watt
Emitting Color of LED Strip	Cool White 8000K
Lumen per Meter	195lm
Protection Degree	IP67

LED Flex-Strip LED-Size
3528


Part No.: **M33A3009** 

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Cuctomor
APPD:	Schumi			FINISH	Jamy		Shee	et No.	1 from 2	Customer:

email: info@edcon-components.com

www.edcon-components.com

# **EDCON-COMPONENTS**











## The Power of LED Light

### **Ordering Informations**

Part-No.
----------

Special ROHS Packing

X R TR

M33A3009

X= No special function	R= ROHS Conform	TR= Tape / Reel		
Turicuon	<b>N</b> = NON ROHS Conform			
		•		

LED Flex-Strip LED-Size 3528

Part No.: **M33A3009** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer:

email: info@edcon-components.com