EDCON-COMPONENTS









Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 4,0mm

Technical Informations

Size of LED	3528				
LED per Meter	48PCS				
Voltage of LED Strip	12Volt				
Power of LED Strip	3,84Watt				
Emitting Color of LED Strip	Cool White 5500K				
Lumen per Meter	312lm				
Protection Degree	IP67				

LED Flex-Strip LED-Size				
3528				

Part No.: **M33A3020**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customor
APPD:	Schumi			FINISH	Jamy		Shee	et No.	1 from 2	Customer:

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.	
----------	--

Special **ROHS Packing** function Χ R TR

M33A3020

R= ROHS TR= Tape / X= No special Conform Reel function N= NON ROHS Conform

> **LED Flex-Strip LED-Size** 3528

Part No.: M33A3020

MATL: DRW: CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Jason Customer: APPD: Schumi FINISH 2 from 2 Sheet No. Jamy