EDCON-COMPONENTS











Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 4,0mm

Technical Informations

Size of LED	3528			
LED per Meter	120PCS			
Voltage of LED Strip	24Volt			
Power of LED Strip	9,6Watt			
Emitting Color of LED Strip	Green			
Lumen per Meter	480lm			
Protection Degree	IP67			

LED Flex-Strip LED-Size 3528


Part No.: **M33A3080**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

Special function ROHS Packing

X R TR

M33A3080

X= No special function

R= ROHS Conform Reel

N= NON ROHS Conform

LED Flex-Strip LED-Size 3528

Part No.: **M33A3080**

MATL: DRW: CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Jason Customer: APPD: Schumi FINISH 2 from 2 Sheet No. Jamy

....