
## **EDCON-COMPONENTS**











### Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 4,0mm

#### **Technical Informations**

Size of LED	3528
LED per Meter	120PCS
Voltage of LED Strip	24Volt
Power of LED Strip	9,6Watt
Emitting Color of LED Strip	Yellow
Lumen per Meter	240lm
Protection Degree	IP67

LED Flex-Strip LED-Size 3528

Part No.: **M33A3082** 

Customer:

DRW: CHKD Wilson MATL: Wilson 06.02.2012 **TOLERANCE** Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

# **EDCON-COMPONENTS**











The Power of LED Light

## **Ordering Informations**

Part-No.
----------

M33A3082

Special function	ROHS	Packing		
Υ	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel
	N= NON	
	ROHS	
	Conform	

LED Flex-Strip LED-Size 3528

Part No.: **M33A3082** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com