
## **EDCON-COMPONENTS**











# Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 5,0mm

### **Technical Informations**

Size of LED	3528	
LED per Meter	48PCS	
Voltage of LED Strip	12Volt	
Power of LED Strip	3,84Watt	
Emitting Color of LED Strip	Red	
Lumen per Meter	96lm	
Protection Degree	IP67 UV	

LED Flex-Strip LED-Size 3528


Part No.: **M33A4001** 

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customor
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2	Customer:

email: info@edcon-components.com

www.edcon-components.com

# **EDCON-COMPONENTS**











# **Ordering Informations**

Part-No.
----------

M33A4001

Special function	ROHS	Packing		
Х	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel		
Turiction	<b>N</b> = NON ROHS Conform			
		='		

**LED Flex-Strip LED-Size** 3528

Part No.: M33A4001

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: