
EDCON-COMPONENTS











Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 5,0mm

Technical Informations

Size of LED	3528			
LED per Meter	60PCS			
Voltage of LED Strip	12Volt			
Power of LED Strip	4,8Watt			
Emitting Color of LED Strip	Cool White 6000K			
Lumen per Meter	390lm			
Protection Degree	IP67 UV			

LED Flex-Strip LED-Size 3528

Part No.: **M33A4021**

										1 411 110
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Cuatamari
APPD:	Schumi			FINISH	Jamv		Sheet No.		1 from 2	Customer:

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

Special **ROHS Packing** function Χ R TR

M33A4021

R= ROHS TR= Tape / X= No special Conform Reel function N= NON ROHS Conform

> **LED Flex-Strip LED-Size** 3528

M33A4021 Part No.:

MATL: DRW: CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Jason APPD: Schumi FINISH 2 from 2 Sheet No. Jamy

Customer: