

# EDCON-COMPONENTS



## Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.  
Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses, buildings, a.s.o.

## Features

Available in DC 12Volt or DC 24Volt maximum  
Operating Temperature: -20°C ~ +50°C  
Long Life span LED light, more than 50000hours  
Viewing Angle of LED 120°  
Available in Different White areas  
2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip  
Length= 5000mm  
Width= 10mm  
Thickness: 5,0mm



The Power of LED Light



## Technical Informations

|                             |                  |
|-----------------------------|------------------|
| Size of LED                 | 3528             |
| LED per Meter               | 60PCS            |
| Voltage of LED Strip        | 12Volt           |
| Power of LED Strip          | 4,8Watt          |
| Emitting Color of LED Strip | Cool White 8000K |
| Lumen per Meter             | 390lm            |
| Protection Degree           | IP67 UV          |

**LED Flex-Strip LED-Size  
3528**

Part No.: **M33A4022**

Customer:

|       |        |      |        |        |        |           |           |          |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 06.02.2012 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 1 from 2 |            |

# EDCON-COMPONENTS



The Power of LED Light



## Ordering Informations

| Part-No. | Special function | ROHS | Packing |  |  |  |
|----------|------------------|------|---------|--|--|--|
| M33A4022 | X                | R    | TR      |  |  |  |

|                        |                     |                 |
|------------------------|---------------------|-----------------|
| X= No special function | R= ROHS Conform     | TR= Tape / Reel |
|                        | N= NON ROHS Conform |                 |

**LED Flex-Strip LED-Size 3528**

Part No.: **M33A4022**

|       |        |      |        |        |        |           |           |          |            |           |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 06.02.2012 | Customer: |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 2 from 2 |            |           |

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)