
EDCON-COMPONENTS











Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 5,0mm

Technical Informations

| Size of LED | 3528 | | |
|--------------------------------|------------------|--|--|
| LED per Meter | 120PCS | | |
| Voltage of LED Strip | 12Volt | | |
| Power of LED Strip | 9,6Watt | | |
| Emitting Color of LED Strip | Cool White 4200K | | |
| Lumen per Meter | 780lm | | |
| Protection Degree | IP67 UV | | |

LED Flex-Strip LED-Size 3528

Part No.: **M33A4045**

Customer:

| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 |
|-------|--------|------|--------|--------|--------|-----------|-------|--------|------------|
| APPD: | Schumi | | | FINISH | Jamy | | Shee | et No. | 1 from 2 |

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

| Part-No. |
|----------|
|----------|

Special function ROHS Packing TR

M33A4045

| X= No special function | R= ROHS Conform | TR= Tape / Reel | | |
|------------------------|--------------------|--------------------|--|--|
| Turiction | N= NON | | | |
| | ROHS | | | |
| | Conform | | | |
| | | • | | |

LED Flex-Strip LED-Size 3528

Part No.: **M33A4045**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com