EDCON-COMPONENTS











Applications

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 5,0mm

Technical Informations

Size of LED	3528		
LED per Meter	120PCS		
Voltage of LED Strip	12Volt		
Power of LED Strip	9,6Watt		
Emitting Color of LED Strip	Cool White 8000K		
Lumen per Meter	780lm		
Protection Degree	IP67 UV		


LED Flex-Strip LED-Size 3528

Part No.: **M33A4048**

										1 411 110
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customor
APPD:	Schumi			FINISH	Jamv		Shee	t No.	1 from 2	Customer:

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

Special function ROHS Packing

X R TR

M33A4048

X= No special function	R= ROHS Conform	TR= Tape / Reel		
Turiction	N= NON			
	ROHS			
	Conform			
		•		

LED Flex-Strip LED-Size 3528

Part No.: **M33A4048**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer:

email: info@edcon-components.com