EDCON-COMPONENTS





COMPONENTS A MEMBER OF EDCON-GROUP

Applications

The Power of LED Light

It is made with Silicon for Outside tube but it is hollow side without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniturre or accent lighting on houses, buildings, a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 5,0mm

| Size of LED | 3528 | |
|--------------------------------|------------------|--|
| LED per Meter | 60PCS | |
| Voltage of LED Strip | 24Volt | |
| Power of LED Strip | 4,8Watt | |
| Emitting Color of LED Strip | Warm White 2400K | |
| Lumen per Meter | 360lm | |
| Protection Degree | IP67 UV | |

Technical Informations

LED Flex-Strip LED-Size 3528 Part No.: M33A4063 DRW: CHKD Wilson MATL: Wilson TOLERANCE 06.02.2012 Mason DATE Jason Customer: APPD: FINISH Schumi Jamy Sheet No. 1 from 2 www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

EDCON-COMPONENTS



The Power of LED Light

REACH ROHS Lead Free



Ordering Informations

| Part-No. | | Special function | ROHS | Packing | | |
|----------|---|------------------|------|---------|--|--|
| | | | | | | |
| M33A4063 | - | Х | R | TR | | |

| X= No special function | R = ROHS Conform | TR= Tape / Reel |
|---------------------------|-----------------------------------|--------------------|
| | N = NON ROHS Conform | |
| | | - |

LED Flex-Strip LED-Size 3528 Part No.: M33A4063 MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com