## **EDCON-COMPONENTS**











## **Applications**

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm

Width: Normal=10mm Small=8mm

Thickness: 4,0mm

### **Technical Informations**

Size of LED	3528	
LED per Meter	30PCS	
Voltage of LED Strip	12Volt	
Power of LED Strip	2,4Watt	
Emitting Color of LED Strip	Blue	
Lumen per Meter	75lm	
Protection Degree	IP68	

LED Flex-Strip LED-Size 3528


Part No.: **M33A5003** 

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	et No.	1 from 2

email: info@edcon-components.com

# **EDCON-COMPONENTS**











The Power of LED Light

## **Ordering Informations**

Part-No.
----------

M33A5003

Width of LED Strip	ROHS	Packing		
N	R	TR		

N= Normal 10mm	R= ROHS Conform	TR= Tape / Reel
(Standard)	N= NON	
<b>M</b> = Medium 8mm	ROHS Conform	

LED Flex-Strip LED-Size 3528

Part No.: **M33A5003** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy