EDCON-COMPONENTS









Applications

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm

Width: Normal=10mm Small=8mm

Thickness: 4,0mm

Technical Informations

Size of LED	3528	
LED per Meter	48PCS	
Voltage of LED Strip	12Volt	
Power of LED Strip	3,84Watt	
Emitting Color of LED Strip	Red	
Lumen per Meter	96lm	
Protection Degree	IP68	

LED Flex-Strip LED-Size 3528


Part No.: **M33A5014**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	et No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

M33A5014

Width of LED Strip	ROHS	Packing		
N	R	TR		

N = Normal	R= ROHS	TR= Tape /
10mm	Conform	Reel
(Standard)	N= NON	
M. Maaliuus	ROHS	
M= Medium 8mm	Conform	
OHIIII		•

LED Flex-Strip LED-Size 3528

Part No.: **M33A5014**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com