

EDCON-COMPONENTS



Applications

It is made with epoxy inside and PVC for outside tube. It's suitable for use in extremely humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

Features

Available in DC 12Volt or DC 24Volt maximum
 Operating Temperature: -20°C ~ +50°C
 Long Life span LED light, more than 50000hours
 Viewing Angle of LED 120°
 Available in Different White areas
 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip
 Length: 5000mm
 Width: Normal=10mm Small=8mm
 Thickness: 4,0mm



The Power of LED Light



Technical Informations

Size of LED	3528
LED per Meter	78PCS
Voltage of LED Strip	12Volt
Power of LED Strip	6,24Watt
Emitting Color of LED Strip	Cool White 8000K
Lumen per Meter	507lm
Protection Degree	IP68

**LED Flex-Strip LED-Size
3528**

Part No.: **M33A5048**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2	

EDCON-COMPONENTS



The Power of LED Light



Ordering Informations

Part-No.	Width of LED Strip	ROHS	Packing			
M33A5048	N	R	TR			

N = Normal 10mm (Standard)	R = ROHS Conform	TR = Tape / Reel
M = Medium 8mm	N = NON ROHS Conform	

**LED Flex-Strip LED-Size
3528**

Part No.: **M33A5048**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2		

www.edcon-components.com

email: info@edcon-components.com