EDCON-COMPONENTS









Applications

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm

Width: Normal=10mm Small=8mm

Thickness: 4,0mm

Technical Informations

| Size of LED | 3528 |
|--------------------------------|------------------|
| LED per Meter | 78PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 6,24Watt |
| Emitting Color of LED Strip | Warm White 2700K |
| Lumen per Meter | 468lm |
| Protection Degree | IP68 |


LED Flex-Strip LED-Size 3528

Part No.: **M33A5051**

| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 | Cuetomori |
|-------|--------|------|--------|--------|--------|-----------|-------|-------|------------|-----------|
| APPD: | Schumi | | | FINISH | Jamy | | Shee | t No. | 1 from 2 | Customer: |

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

| Part-No. |
|----------|
|----------|

M33A5051

| Width of LED Strip | ROHS | Packing | | |
|-----------------------|------|---------|--|--|
| | | | | |
| N | R | TR | | |

| N= Normal | R= ROHS | TR= Tape / |
|--------------------------|---------|------------|
| 10mm | Conform | Reel |
| (Standard) | N= NON | |
| M. Madium | ROHS | |
| M = Medium 8mm | Conform | |
| OITIIII | | =' |

LED Flex-Strip LED-Size 3528

Part No.: **M33A5051**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com