EDCON-COMPONENTS







Applications

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

Features

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length: 5000mm Width: Normal=10mm Small=8mm Thickness: 4,0mm


Technical	Informations

Size of LED	3528	
LED per Meter	120PCS	
Voltage of LED Strip	12Volt	
Power of LED Strip	9,6Watt	
Emitting Color of LED Strip	Cool White 10000K	
Lumen per Meter	780lm	
Protection Degree	IP68	

											Strip LED-Size 3528
										Part No.:	M33A5062
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2		
www.edcon-c	www.edcon-components.com email: info@edcon-components.com										

Copyright by EDCON-COMPONENTS

EDCON-COMPONENTS



The Power of LED Light

REACH



Ordering Informations

Part-No.		Width of LED Strip	ROHS	Packing		
	_					
M33A5062] -	N	R	TR		

R = ROHS Conform	TR = Tape / Reel
N= NON	
ROHS Conform	
	N= NON ROHS

LED Flex-Strip LED-Size 3528 Part No.: M33A5062 CHKD MATL: DRW: Jason Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com