


EDCON-COMPONENTS



The Power of LED Light



Applications

It is made with epoxy inside and PVC for outside tube. It's suitable for use in extremely humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

Features

Available in DC 12Volt or DC 24Volt maximum
 Operating Temperature: -20°C ~ +50°C
 Long Life span LED light, more than 50000hours
 Viewing Angle of LED 120°
 Available in Different White areas
 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip
 Length: 5000mm
 Width: Normal=10mm Small=8mm
 Thickness: 4,0mm

Technical Informations

| | |
|-----------------------------|------------------|
| Size of LED | 3528 |
| LED per Meter | 120PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 9,6Watt |
| Emitting Color of LED Strip | Warm White 2700K |
| Lumen per Meter | 720lm |
| Protection Degree | IP68 |

**LED Flex-Strip LED-Size
3528**

Part No.: **M33A5064**

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 1 from 2 |

Customer:

EDCON-COMPONENTS



The Power of LED Light



Ordering Informations

| Part-No. | Width of LED Strip | ROHS | Packing | | | |
|----------|--------------------|------|---------|--|--|--|
|----------|--------------------|------|---------|--|--|--|

| | | | | | | |
|----------|---|---|----|--|--|--|
| M33A5064 | N | R | TR | | | |
|----------|---|---|----|--|--|--|

| | | |
|---|-----------------------------------|----------------------------|
| N = Normal 10mm (Standard) | R = ROHS Conform | TR = Tape / Reel |
| M = Medium 8mm | N = NON ROHS Conform | |

**LED Flex-Strip LED-Size
3528**

Part No.: **M33A5064**

| | | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 06.02.2012 | Customer: |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 2 from 2 | | |

www.edcon-components.com

email: info@edcon-components.com