## **EDCON-COMPONENTS**







### Applications

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length: 5000mm Width: Normal=10mm Small=8mm Thickness: 4,0mm

rechnica	matio	15


To a la usia a la Jua fa una

Size of LED	3528		
LED per Meter	60PCS		
Voltage of LED Strip	24Volt		
Power of LED Strip	4,8Watt		
Emitting Color of LED Strip	Warm White 2700K		
Lumen per Meter	360lm		
Protection Degree	IP68		

											Strip LED-Size 3528
										Part No.:	M33A5077
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012	Customer:	
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2	Customer.	
www.edcon-components.com email: info@edcon-components.com											

## Copyright by EDCON-COMPONENTS

# **EDCON-COMPONENTS**



The Power of LED Light

REACH ROHS Lead Free



**Ordering Informations** 

Part-No.		Width of LED Strip	ROHS	Packing		
	_					
M33A5077	-	N	R	TR		

<b>N</b> = Normal 10mm	<b>R</b> = ROHS Conform	<b>TR</b> = Tape / Reel		
(Standard)	N= NON			
<b>M</b> = Medium 8mm	ROHS Conform			

LED Flex-Strip LED-Size 3528 Part No.: M33A5077 CHKD MATL: DRW: Jason Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com