## **EDCON-COMPONENTS**









## **Applications**

It is made with epxy inside and PVC for outside tube. It's suitable for use in extremly humid environments such as swimming pools, saunas or outdoor use where direct contact with rain or water is unavoidable.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm

Width: Normal=10mm Small=8mm

Thickness: 4,0mm

### **Technical Informations**

Size of LED	3528	
LED per Meter	60PCS	
Voltage of LED Strip	24Volt	
Power of LED Strip	4,8Watt	
Emitting Color of LED Strip	Warm White 3000K	
Lumen per Meter	360lm	
Protection Degree	IP68	

LED Flex-Strip LED-Size 3528


Part No.: **M33A5078** 

Customer:

DRW: CHKD Wilson MATL: Wilson TOLERANCE 06.02.2012 Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

# **EDCON-COMPONENTS**











The Power of LED Light

## **Ordering Informations**

Part-No.
----------

M33A5078

Width of LED Strip	ROHS	Packing		
N	R	TR		

<b>N</b> = Normal 10mm	R= ROHS Conform	TR= Tape / Reel	
(Standard)	N= NON		
<b>M</b> = Medium 8mm	ROHS Conform		

LED Flex-Strip LED-Size 3528

Part No.: **M33A5078** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

0111011