


EDCON-COMPONENTS



The Power of LED Light



Applications

Ideal for indoor applications, like under cupboards, stairs, indirect lighting applications a.s.o.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm

Width: 10mm

Thickness: 2,5mm

Technical Informations

| | |
|-----------------------------|------------------|
| Size of LED | 5050 |
| LED per Meter | 60PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 14,4Watt |
| Emitting Color of LED Strip | Cool White 6000K |
| Lumen per Meter | 900~1170lm |
| Protection Degree | IP20 |

**LED Flex-Strip LED-Size
5050**

Part No.: **M33A7022**

Customer:

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 07.02.2012 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 1 from 2 |

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



The Power of LED Light



Ordering Informations

| Part-No. | Special function | ROHS | Packing | | | |
|----------|------------------|------|---------|--|--|--|
| M33A7022 | X | R | TR | | | |

| | | |
|------------------------|---------------------|-----------------|
| X= No special function | R= ROHS Conform | TR= Tape / Reel |
| | N= NON ROHS Conform | |

LED Flex-Strip LED-Size 5050

Part No.: **M33A7022**

| | | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 07.02.2012 | Customer: |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 2 from 2 | | |

www.edcon-components.com

email: info@edcon-components.com