EDCON-COMPONENTS











Applications

It is made with Epoxy cover, Suitable for use in humid locations such as bathroom and for use outdoors, for example on garden furniture or accentlighting on houses and buildings.

Features

Available in DC 12Volt or DC 24Volt maximum
Operating Temperature: -20°C ~ +50°C
Long Life span LED light, more than 50000hours
Viewing Angle of LED 120°
Available in Different White areas
2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 2,5mm

Technical Informations

Size of LED	5050
LED per Meter	30PCS
Voltage of LED Strip	12Volt
Power of LED Strip	7,2Watt
Emitting Color of LED Strip	Green
Lumen per Meter	360lm
Protection Degree	IP65

LED Flex-Strip LED-Size 5050


Part No.: **M33A8002**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	et No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

M33A8002

Special function	ROHS	Packing		
Χ	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel		
Turiction	N = NON ROHS			
	Conform			
		•		

LED Flex-Strip LED-Size 5050

Part No.: **M33A8002**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: