EDCON-COMPONENTS











Applications

It is made with Epoxy cover, Suitable for use in humid locations such as bathroom and for use outdoors, for example on garden furniture or accentlighting on houses and buildings.

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 2,5mm

Technical Informations

| Size of LED | 5050 |
|--------------------------------|------------------|
| LED per Meter | 30PCS |
| Voltage of LED Strip | 12Volt |
| Power of LED Strip | 7,2Watt |
| Emitting Color of LED Strip | Cool White 8000K |
| Lumen per Meter | 450~585lm |
| Protection Degree | IP65 |

LED Flex-Strip LED-Size 5050


Part No.: **M33A8009**

Customer:

DRW: CHKD Wilson MATL: Wilson TOLERANCE Mason 07.02.2012 DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

| Part-No. |
|----------|
|----------|

M33A8009

| Special function | ROHS | Packing | | |
|------------------|------|---------|--|--|
| | | | | |
| Х | R | TR | | |

| X= No special function | R= ROHS Conform | TR= Tape / Reel |
|------------------------|------------------------|--------------------|
| Turicuon | N = NON ROHS | |
| | Conform | |
| | | • |

LED Flex-Strip LED-Size 5050

Part No.: **M33A8009**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

omor.