
## **EDCON-COMPONENTS**











## **Applications**

It is made with Epoxy cover, Suitable for use in humid locations such as bathroom and for use outdoors, for example on garden furniture or accentlighting on houses and buildings.

#### **Features**

Available in DC 12Volt or DC 24Volt maximum
Operating Temperature: -20°C ~ +50°C
Long Life span LED light, more than 50000hours
Viewing Angle of LED 120°
Available in Different White areas
2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 2,5mm

### **Technical Informations**

Size of LED	5050	
LED per Meter	60PCS	
Voltage of LED Strip	12Volt	
Power of LED Strip	14,Watt	
Protection Degree	IP65	

Emitting Color of LED Strip	Lumen per Meter	
Red	120lm	
Green	240lm	
Blue	150lm	

LED Flex-Strip LED-Size 5050


Part No.: **M33A8028** 

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2

email: info@edcon-components.com

# **EDCON-COMPONENTS**











The Power of LED Light

## **Ordering Informations**

Part-No.
----------

M33A8028

Special function	ROHS	Packing		
V	D	TD		

V_ No appoint	R= ROHS	TR= Tape /	
X= No special function	Conform	Reel	
Turiction	N= NON		
	ROHS		
	Conform		
		-	

LED Flex-Strip LED-Size 5050

Part No.: **M33A8028** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy